



SERIOUS ABOUT LAUNDRY.

SINGLE TUMBLE DRYERS 25-35 LB & STACK TUMBLE DRYERS 30-45 LB

MODELS	UT25	UT30	UT35	UTT30	UTT45
Control Option	UniLinc™ Programmable Control Dual Digital Timers	UniLinc™ Programmable Control Dual Digital Timers	UniLinc™ Programmable Control Dual Digital Timers	Programmable Control Dual Digital Timers	Programmable Control Dual Digital Timers
Dry Weight Capacity - lb (kg)	25 (11.3)	30 (13.6)	35 (15.9)	2 x 30 (13.6)	2 x 45 (20.4)
Cylinder Size - in (mm) (diameter x depth)	26 1/2 x 24 (673 x 610)	26 1/2 x 30 (673 x 762)	30 x 30 (762 x 762)	30 x 26 (762 x 660)	33 x 30 (838 x 762)
Cylinder Volume - cu. ft. (liters)	7.7 (217)	9.6 (271)	12.3 (347)	10.6 (301)	14.8 (421)
Width - in (mm)	28 (711)	28 (711)	31 1/2 (800)	31 1/2 (800)	34 1/2 (876)
Depth - in (mm)	40 7/8 (1038)	46 7/8 (1191)	46 7/8 (1191)	42 7/8 (1086)	48 7/8 (1235)
Height - in (mm)	63 7/8 (1622)*	63 7/8 (1622)*	63 7/8 (1622)*	76 1/4 (1937)	81 1/4 (2064)
Motor - HP (W)	1/4 (187)	1/4 (187)	1/4 (187)	2 x 1/4 (187)	2 x 1/2 (373)
Air Outlet Diameter - in (mm)	6 (152)	6 (152)	8 (203)	1 x 8 (203)	1 x 10 (254)
Airflow - cfm (liters/sec)	60 Hz: 500 (236) 50 Hz: 430 (203)	60 Hz: 500 (236) 50 Hz: 430 (203)	60 Hz: 650 (307) 50 Hz: 550 (260)	60 Hz: 2 x 400 (189) 50 Hz: 2 x 340 (160)	60 Hz: 2 x 600 (283) 50 Hz: 2 x 500 (236)
Reversing Cylinder	Option	Option	Option	Not available	Not available
Water Inlet Size (C.A.R.E. System)	(1) 3/4"-11 1/2" NH Hose Conn.	(1) 3/4"-11 1/2" NH Hose Conn.	(1) 3/4"-11 1/2" NH Hose Conn.	N/A	N/A
Plumbing Connection - in (mm)	Gas Models - 1/2" NPT (13) Steam Models - 1/2" NPT (19)	Gas Models - 1/2" NPT (13) Steam Models - 3/4" NPT (19)	Gas Models - 1/2" NPT (13) Steam Models - 3/4" NPT (19)	Gas Models - 1/2" NPT (13) Steam Models - 3/4" NPT (19)	Gas Models - 1/2" NPT (13) Steam Models - N/A
Energy Data	Gas Models - 64,000 Btu/hr (18.6 kW) Steam Models - At 100 psi (6.9 bar): 3.9 BHP, 134,700 Btu/hr (39.6 kW) Electric Models - 12 kW	Gas Models - 73,000 Btu/hr (21.4 kW) Steam Models - At 100 psi (6.9 bar): 3.9 BHP, 134,700 Btu/hr (39.6 kW) Electric Models - 21 kW	Gas Models - 90,000 Btu/hr (26.4 kW) Steam Models - At 100 psi (6.9 bar): 4.8 BHP, 166,000 Btu/hr (48.6 kW) Electric Models - 24 kW	Gas Models per Pocket - 73,000 Btu/hr (21.4 kW) Steam Models per Pocket - At 100 psi (6.9 bar): 3.2 BHP, 111,000 Btu/hr (32.5 kW) Electric Models per Pocket - 21 kW	Gas Models per Pocket - 95,000 Btu/hr (27.8 kW) Steam Models per Pocket - N/A Electric Models per Pocket - N/A
Electrical Specifications	Gas and Steam Models - Amps 100/200-220/60/1 11/5.8 120/208-240/60/1 12/6.7 200-208/240/60/3 3.2/3.2 380/60/3 1.5 460-480/60/3 1.6 100/200/50/1 12.1/7.5 230-240/50/1 7.5 200/50/3 2.9 230-240/50/3 3.5 380/400-415/50/3 1.5/1.6 Electric Models - 208/60/1 64 240/60/1 57 200/60/1 64 200-208/60/3 37 240/60/3 33 380/60/3 20 460-480/60/3 16 200/50/1 63 230-240/50/1 58 200/5/3 36 230-240/50/3 33 380/50/3 20 400-415/50/3 18	Gas and Steam Models - Amps 100/200-220/60/1 11/5.8 120/208-240/60/1 12/6.7 200-208/240/60/3 3.2/3.2 380/60/3 1.5 460-480/60/3 1.6 100/200/50/1 12.1/7.5 230-240/50/1 7.5 200/50/3 2.9 230-240/50/3 3.5 380/400-415/50/3 1.5/1.6 Electric Models - 208/60/1 108 240/60/1 94 200/60/1 106 200-208/60/3 62 240/60/3 54 380/60/3 33 460-480/60/3 27 200/50/1 105 230-240/50/1 95 200/5/3 60 230-240/50/3 55 380/50/3 33 400-415/50/3 31	Gas and Steam Models - Amps 100/200-220/60/1 11/5.8 120/208-240/60/1 12/6.7 200-208/240/60/3 3.2/3.2 380/60/3 1.5 460-480/60/3 1.6 100/200/50/1 12.1/7.5 230-240/50/1 7.5 200/50/3 2.9 230-240/50/3 3.5 380/400-415/50/3 1.5/1.6 Electric Models - 208/60/1 122 240/60/1 107 200/60/1 122 200-208/60/3 71 240/60/3 62 380/60/3 38 460-480/60/3 31 200/50/1 119 230-240/50/1 108 200/5/3 65 230-240/50/3 62 380/50/3 38 400-415/50/3 35	Gas and Steam Models - Amps 100/200-220/60/1 22/11.6 120/208-240/60/1 16/8.0 200-208/240/60/3 6.4/6.4 380/60/3 3.0 460-480/60/3 3.3 100/200/50/1 24.2/15.0 230-240/50/1 15.0 200/50/3 5.8 230-240/50/3 7.0 380/400-415/50/3 3.0/3.2 Electric Models - 200-208/60/3 62 x 2 240/60/3 54 x 2 380/60/3 33 x 2 460-480/60/3 27 x 2 200/50/3 60 x 2 230-240/50/3 55 x 2 380/50/3 33 x 2 400-415/50/3 31 x 2	Gas Models - Amps 200-208/240/60/3 9.6/9.6 208-240/60/1 12.0 200/50/1 11.2 230-240/50/1 10.8
Net Weight - lb (kg)	300 (137)	330 (150)	360 (163)	544 (247)	673 (305)
Shipping Weight - lb (kg)	332 (151)	364 (165)	394 (179)	582 (264)	718 (326)
Agency Approvals**	CSA, CE	CSA, CE	CSA, CE	CSA, CE	CSA, CE



To learn more, or to find a distributor in your area, visit UNIMAC.COM
Alliance Laundry Systems - Shepard St, Ripon WI 54971 - 1.800.587.5458

* Also available in optional heights of 72 1/4" (1835 mm) and 78 1/4" (1937 mm). ** Complies with international Electro-Magnetic Compatibility (EMC) Standards. Commercial dryer models are made to suit a variety of electrical service characteristics. See your UniMac® distributor for specifications. For further details on installation, refer to Installation, Operation and Maintenance instructions supplied with the commercial dryer.

For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications are subject to change without notice. The quality management system of Alliance Laundry Systems® Ripon facility has been registered to ISO 9001:2008. Copyright 2014 Alliance Laundry Systems LLC. Printed in the U.S.A.



SERIOUS ABOUT LAUNDRY.