

UW105



THE UW SERIES GETS MORE DONE IN LESS TIME

With our redesigned UW hardmount washer-extractors, UniMac® gives you more ways to improve the efficiency of your laundry room. With 300 G-Force extraction, they deliver extremely fast dry times. Combined with advanced UniLinc™ controls and OPTispray™ Rinsing Technology, these machines increase your productivity better than any other machine on the market.

INCREASED CAPACITY

5-10 lb larger capacity than older UW models so you can wash more in every load.

DECREASED FOOTPRINT

Smaller footprint means these machines take up less space in your laundry room.

IMPROVED DOOR

Rugged hinge and handle paired with a proven roll pin/cam door lock system allows for smooth open-and-close operation.

ENLARGED DOOR OPENING

Larger door openings allow you to get loads in and out faster, improving your productivity compared to competitor brands.

NEW MODELS

UW85 and 105

UW130 and 160

OLD MODELS

UW80 and 100

UW125

COMPETITOR MODELS

COMPETITOR 80 and 100

COMPETITOR 140 and 160

DIAMETER

21"

24.8"

17.5"

20"

18"

20"



WORLD-CLASS SUPPORT

At UniMac, we're committed to our customers. We want to be sure that every product we manufacture continuously meets your needs and helps your business succeed. It's the reason why every machine comes with an industry-leading warranty for peace of mind, along with comprehensive support from the largest, most knowledgeable and responsive distributor network in the industry.

WARRANTY

A five-year warranty covers the frame, basket, shaft, bearings and seals from failure or breakage during normal operation due to defects in material or workmanship. A limited three-year warranty is offered on all other parts.

SERVICE PARTS AVAILABILITY

FACTORY-TRAINED TECHNICIANS AND GLOBAL DISTRIBUTION NETWORK

SERVICE TRAINING CERTIFICATION FOR DISTRIBUTORS

INDUSTRY-LEADING, LAUNDRY-FOCUSED FINANCING

LAUNDRY DESIGN SERVICES

REDESIGNED UW HARDMOUNT WASHER-EXTRACTORS 85-160 LB – UNILINC™ AND M30 CONTROLS

SPECIFICATIONS		UW85		UW105		UW130		UW160
Capacity - lb (kg)		85 (38.5)		105 (47.6)		130 (60)		160 (72.6)
Cylinder Diameter - in (mm)		36 (914)		36 (914)		42 (1067)		42 (1067)
Cylinder Depth - in (mm)		22 (559)		27 (686)		24 1/2 (622)		30 (762)
Cylinder Volume - cu. ft. (liters)		13 (368)		15.9 (450)		19.6 (555)		24.1 (682)
Width - in (mm)		40 1/8 (1019)		40 1/8 (1019)		46 1/8 (1171)		46 1/8 (1171)
Depth - in (mm)		51 1/2 (1308)		56 1/2 (1435)		54 1/2 (1384)		60 (1524)
Height - in (mm)		67 19/32 (1717)		67 19/32 (1717)		72 5/8 (1844)		72 5/8 (1844)
Door Opening Size - in (mm)		21 (533)		21 (533)		24 13/16 (630)		24 13/16 (630)
Door Bottom to Floor - in (mm)		28 1/8 (713)		28 1/8 (713)		29 13/16 (758)		29 13/16 (758)
Motor Size - HP (kW)		7.5 (5.6)		7.5 (5.6)		10 (7.5)		10 (7.5)
Control Options		UniLinc™	M30	UniLinc™	M30	UniLinc™	M30	UniLinc™
Total # of Speeds		V Sp	M Sp	V Sp	M Sp	V Sp	M Sp	V Sp
		8	6	8	6	8	6	8
Cylinder Speed RPM (G-Force)	Gentle	28 (.40)	28 (.40)	28 (.40)	28 (.40)	26 (.40)	26 (.40)	26 (.40)
	Wash	39 (.78)	39 (.78)	39 (.78)	39 (.78)	36 (.77)	36 (.77)	36 (.77)
	Distribution	70 (2.5)	70 (2.5)	70 (2.5)	70 (2.5)	65 (2.5)	65 (2.5)	65 (2.5)
	Very Low Extract	230 (27)	230 (27)	230 (27)	230 (27)	213 (27)	213 (27)	213 (27)
	Low Extract	443 (100)	443 (100)	443 (100)	443 (100)	410 (100)	410 (100)	410 (100)
	Medium Extract	626 (200)	626 (200)	626 (200)	626 (200)	579 (200)	579 (200)	579 (200)
	High Extract	700 (250)	–	700 (250)	–	648 (250)	–	648 (250)
Very High Extract	766 (300)	–	766 (300)	–	710 (300)	–	710 (300)	
Drain Diameter - in (mm)		2 @ 3 (76)	1 @ 3 (76)	2 @ 3 (76)	1 @ 3 (76)	2 @ 3 (76)	1 @ 3 (76)	2 @ 3 (76)
Steam Connection - in (mm)		1/2 (13)		1/2 (13)		3/4 (19)		3/4 (19)
Water Inlet Connection - in (mm)		4 @ 3/4 (19)	2 @ 3/4 (19)	4 @ 3/4 (19)	2 @ 3/4 (19)	2 @ 1 (25) + 2 @ 3/4 (19)	2 @ 1 (25)	2 @ 1 (25) + 2 @ 3/4 (19)
Shipping Dimensions - in (mm)	Width	43 3/16 (1097)		43 3/16 (1097)		49 3/16 (1250)		49 3/16 (1250)
	Depth	61 13/16 (1570)		61 13/16 (1570)		64 13/16 (1646)		64 13/16 (1646)
	Height	69 3/8 (1763)		69 3/8 (1763)		76 3/8 (1941)		76 3/8 (1941)
Net Weight - lb (kg)		1670 (757)		1700 (771)		2040 (925)		2070 (939)
Standard Shipping Weight - lb (kg)		1720 (780)		1750 (794)		2100 (953)		2130 (966)
Slat Crate Shipping Weight - lb (kg)		1870 (848)		1900 (862)		2260 (1025)		2290 (1039)
Agency Approvals		cETLus, CE		cETLus, CE		cETLus, CE		cETLus, CE

To learn more, or to find a distributor in your area, visit UNIMAC.COM
Alliance Laundry Systems - Shepard St, Ripon WI 54971 - 1.800.587.5458

Consult your UniMac® distributor for details. For the most accurate information, the installation guide should be used for all design and construction purposes. Due to continuous product improvements, design and specifications subject to change without notice. The quality management systems at Alliance Laundry Systems' Ripon facility has been registered to ISO 9001:2008.

©2014 Alliance Laundry Systems LLC.

Printed in the U.S.A.



SERIOUS ABOUT LAUNDRY.

